

# ENSTO

## Coupler

NAC21SL.W



Code	NAC21SL.W
GTIN	6418677114861
Name	Coupler EnstoNet
Description	2-pole screw coupler, plug, with strain-relief, low, white (1, N)
Vendor	Ensto Building Systems Finland Oy

## Technical specification

### Classification Group

Color:	White
Conductor cross-section:	0,75 - 4 mm <sup>2</sup>
Degree of protection:	IP20
Dimensions l x w x h:	51 x 29 x 20 mm
Material:	Polyamide 66
Operating temperature max:	70 °C
Installation temperature min:	5 °C
Operating temperature min:	-30°C without mechanical stress
Pole markings:	1,N
Rated current:	20 A
Rated voltage:	250 ... 250 V
UL Rated current:	16 A
UL Rated voltage:	250 V
UL Wire Size:	12 ... 18

### Others

ETIM Class:	EC002560
-------------	----------

### Dimensions

Length:	51 mm
Width:	29 mm
Height:	20 mm
Weight:	0.012 kg

## ETIM 7 Technical specification

---

### etim

Rated current:	20 A
Number of poles:	2
Degree of protection (IP):	IP20
Connection type:	Screw connection
Model:	Plug
Cable diameter:	4 ... 10.5 mm
Connection cross section (fine-strand):	0.75 ... 4 mm <sup>2</sup>
Connection cross section (solid-core):	0.75 ... 4 mm <sup>2</sup>
Number of connections per pole:	1
Pole codification:	L, N
Mechanical coding:	True
Colour coding/contact insert:	White
Locking mechanism:	Integrated in plug-in connector
With strain relief:	True
Max. continuous temperature resistance contact part:	70 °C
Max. continuous temperature resistance strain relief:	70 °C
Material housing:	Polyamide (PA)
Halogen free:	True
Contact material:	CuZn
Surface finish contacts:	Silver-plated
Pollution degree:	2
Rated surge voltage:	4 kV
Length:	51 mm
Height:	20 mm
Width:	29 mm

## Packaging

---

### Pallet package

Unit:	PCE
Package size:	12600

### Default package

Unit:	PCE
Package size:	200
Depth:	383 mm
Width:	258 mm

Height:	131 mm
Weight:	2.616 kg
Volume:	12.944634 l