

# ENSTO

## Coupler

NCC21.G

Code	NCC21.G
GTIN	6418677117336
Name	Coupler EnstoNet Grey (a+, b-)
Description	
Vendor	Ensto Building Systems Finland Oy



## Technical specification

### Classification Group

Color:	Grey
Conductor cross-section:	0,75 - 4 mm <sup>2</sup>
Degree of protection:	IP20
Dimensions l x w x h:	32 x 29 x 18 mm
Flammability rating:	UL 94 V-2
Material:	Polyamide 66
Operating temperature max:	70 °C
Installation temperature min:	5 °C
Operating temperature min:	-30°C without mechanical stress
Pole markings:	a+,b-
Rated current:	20 A
Rated voltage:	250 ... 250 V
UL Rated current:	16 A
UL Rated voltage:	250 V
UL Wire Size:	12 ... 18

### Others

ETIM Class:	EC002566
-------------	----------

### Dimensions

Length:	32 mm
Width:	29 mm
Height:	18 mm
Weight:	0.0066 kg

## ETIM 7 Technical specification

### etim

Rated voltage:	250 V
Rated current:	20 A
Number of poles:	2
Degree of protection (IP):	IP20
Connection type:	Screw connection
Model:	Plug
Built-in version:	Built-in part/plug-in connection
Angle of plug:	Straight
Connection size thread:	M3
Connection cross section (fine-strand):	0.75 ... 4 mm <sup>2</sup>
Connection cross section (solid-core):	0.75 ... 4 mm <sup>2</sup>
Number of connections per pole:	1
Mechanical coding:	True
Colour coding/contact insert:	Grey
Colour of the separate adapter piece:	Without adapter piece
Colour housing:	Grey
Locking mechanism:	Integrated in plug-in connector
Max. continuous temperature resistance contact part:	70 °C
Max. continuous temperature resistance strain relief:	70 °C
Material housing:	Polyamide (PA)
Halogen free:	True
Contact material:	CuZn
Surface finish contacts:	Silver-plated
Pollution degree:	2
Rated surge voltage:	4 kV
Length:	32 mm
Height:	18 mm
Width:	29 mm

### Packaging

#### Pallet package

Unit:	PCE
Package size:	31500

#### Default package

Unit:	PCE
Package size:	500
Depth:	383 mm
Width:	258 mm
Height:	131 mm
Weight:	3.516 kg

**Volume:**

12.944634 l